

SEED GERMINATION AND PLANT SUPPORTING UTILITY

By: Raymond E. Umbaugh, Jr.

SEED GERMINATION AND PLANT SUPPORTING UTILITY

Field of the Invention

This invention relates to plant propagating apparatus and methods, and, more particularly, relates to
5 such apparatus for plant culture in the absence of root supporting growth media such as soil or the like.

Background of the Invention

A variety of growing methods and systems for use in the field of aeroponics and/or hydroponics have been
10 heretofore suggested and/or utilized. These methods and systems have employed various means for germinating seeds and for supporting seedlings and plants during their growth cycle. Such means as have been heretofore employed have often required transplanting of a seedling
15 once germinated (risking plant damage), and/or have not adequately addressed plant support over the lifecycle of the plant.

Support of the growing plant is of particular concern in culture where no root anchoring growth medium
20 (such as soil or the like) is present, and must be addressed to better assure proper development of the plant. Heretofore utilized arrangements have often required plant support to be reconfigured multiple times

during the growth of the plant from seedling to full term.

As may be appreciated, therefore, improvement of systems for seed germination and support of plants in
5 aeroponic and/or hydroponic culture could be utilized. In particular, it would be beneficial to provide systems wherein handling of plants from seed germination to full term growth is minimized or eliminated.

Summary of the Invention

10 This invention provides a seed germination and plant supporting utility that allows a seed germinated utilizing the utility to grow to full term in the same utility without benefit of root supporting plant growth media. The utility thus minimizes or eliminates handling
15 of the plant during its growth cycle, and will be particularly useful in aeroponic growing systems, hydorponic growing systems, and/or for seed germination and initial seedling growth in preparation for planting. In most applications, the utility provides adequate
20 support for a plant over its full growth cycle (from seedling to full term) without need for plant support reconfiguration.

The germination and supporting utility includes a spacer having a central opening defining a passageway therethrough between spacer ends, or sides. Mesh is maintained at both sides of the spacer so that the mesh
5 is held spaced apart a selected distance and the central opening is enshrouded by the mesh.

The spacer is preferably ring shaped, having an inside diameter and outside diameter. The mesh preferably includes at least first and second fiber mesh
10 swathes each with a diameter greater than the inside diameter of the spacer and positioned at different ones of the opposite sides of the spacer. Means are preferably provided for retaining utility assemblage at each of the opposite ends of the spacer ring.

15 The retaining means preferably utilize first and second retainers (removable ring shaped retainer caps, for example) associable with the spacer at the first and second ends thereof adjacent to the mesh. Each of the retainers has an opening therethrough in correspondence
20 with the spacer passageway when associated with the spacer, and, in at least one embodiment of this invention, serve to anchor the mesh at the spacer.

It is therefore an object of this invention to provide a seed germination and plant supporting utility.

It is another object of this invention to provide a seed germination and plant supporting utility that allows a seed germinated utilizing the utility to grow to full term in the same utility without root supporting plant growth media.

It is another object of this invention to provide a seed germination and plant supporting utility that minimizes or eliminates handling of the plant during its growth cycle.

It is still another object of this invention to provide a seed germination and plant supporting utility that is particularly useful in aeroponic growing systems, hydorponic growing systems, and/or for seed germination and initial seedling growth in preparation for planting.

It is yet another object of this invention to provide a seed germination and plant supporting utility that provides adequate support for a plant over its full growth cycle (from seedling to full term) without need for plant support reconfiguration.

It is another object of this invention to provide a seed germination and plant supporting utility that includes a spacer having a central opening therethrough between sides of the spacer, and mesh maintained at both of the sides of the spacer, wherein the mesh is held

spaced apart a selected distance by the spacer and enshrouds the central opening.

It is still another object of this invention to provide a seed germination and plant supporting utility including at least a first spacer having a passageway therethrough between first and second ends of the first spacer, a first mesh swathe positioned at the first end of the first spacer, a second mesh swathe positioned at the second end of the first spacer, and first and second retainers associable with the first spacer at the first and second ends thereof, respectively, adjacent to the first and second mesh swathes positioned thereat, each of the retainers having an opening therethrough in correspondence with the first spacer passageway when associated with the first spacer.

It is yet another object of this invention to provide a seed germination and plant supporting utility including a spacer ring having a central opening therethrough between opposite ends of the spacer ring, the spacer ring having an inside diameter adjacent the central opening and outside diameter, first and second mesh each with a diameter greater than the inside diameter of the spacer ring and each positioned at a different one of the opposite ends of the spacer ring,

and retaining means operative at each of the opposite ends of the spacer ring for maintaining utility assemblage.

5 With these and other objects in view, which will become apparent to one skilled in the art as the description proceeds, this invention resides in the novel construction, combination, and arrangement of parts substantially as hereinafter described, and more particularly defined by the appended claims, it being
10 understood that changes in the precise embodiment of the herein disclosed invention are meant to be included as come within the scope of the claims.

Brief Description of the Drawings

The accompanying drawings illustrate a complete
15 embodiment of the invention according to the best mode so far devised for the practical application of the principles thereof, and in which:

FIGURE 1 is a perspective view of a aeroponic growing system employing a number of the germination and
20 supporting utilities of this invention;

FIGURE 2 is a perspective view of a first embodiment of one utility of this invention;

FIGURE 3 is an exploded view of the utility
illustrated in FIGURE 2;

FIGURE 4 is an exploded view of a second embodiment
of a utility of this invention;

5 FIGURE 5A is an exploded view of the containment and
feeding apparatus of the system of FIGURE 1;

FIGURE 5B is an exploded view of the positioning
structure of the system of FIGURE 1 including several
utility maintenance platforms;

10 FIGURE 6 is an exploded view of one embodiment of
the utility maintenance platforms of FIGURE 5B;

FIGURE 7 is an exploded view of a second embodiment
of the utility maintenance platforms of FIGURE 5B in
combination to provide another configuration of the
15 utility of this invention;

FIGURE 8 is an exploded view of a cutting
maintenance platform as also shown in FIGURE 5B;

FIGURE 9 is a perspective view of a second
embodiment of a cutting maintenance platform; and

20 FIGURE 10 is a perspective of the cutting
maintenance platform of FIGURE 9 opened for cutting
insertion or removal.

Description of th Invention

A multi-element seed germination and plant supporting utility 17 is shown in FIGURE 1, in an aeroponic growing system 19 in this particularly embodiment (it being understood that the utility, or portions thereof, could as well be employed in hydroponic systems and/or for seed germination applications).

Utility 17, in such an aeroponic growing system 19, would include a containment and feeding apparatus 21 having removable plant positioning structure 23 configured to be received at the upper opening 24 therein (FIGURE 5A).

Multiple receiving stations 25 are provided at structure 23 for receipt of variously configured plant maintenance platforms 27 and or filler blanks 29, all as will be described in greater detail hereinbelow.

Turning to FIGURES 2 and 3, a first embodiment of a utility 31 of the seed germination and plant supporting utility 17 of this invention primarily of concern herein is shown. Utility portion 31 includes upper fiber mesh swathe 33 and lower fiber mesh swath 34 held at ends (or sides) 35 and 37 of spacer 39 having a central opening 41 therethrough defining a passageway. As utilized herein, the term mesh implies any interlocking or intertwining

arrangement, construction or other network of material or structure that defines a network of spaces. Mesh 33 and 34 can be any material suitable to the task, including metal, thermoplastic or fabric (nylon, for example) screen, but is preferably cotton or other expandable and degradable fiber material.

While mesh 33 and 34 are shown as two separate elements, it should be appreciated that a single mesh swathe encompassing both ends 35 and 37 of spacer 39 could be utilized. Mesh 33 and 34 can be retained at spacer 39 in any convenient manner (gluing, welding or the like would be acceptable), but utility assemblage in this embodiment is preferably maintained utilizing removable retainers 45 and 47 which anchor mesh 33 and 34 at spacer ends 35 and 37.

This configuration of utility 31 provides a seed germination pod, or module, that supports a seedling (51) to full growth after germination. Mesh 33/34 is held spaced apart a selected distance by spacer 39 and enshrouds passageway 41. Mesh 33 is preferably more loosely fit at spacer 39 than mesh 34 to provide a seed centering sag at mesh 33, and preferably has a mesh size greater than the mesh size of mesh 34. As a seed deposited on upper mesh 33 develops its first roots

during germination, the roots grow through mesh 33 with little resistance down through passageway 41 of spacer 39 to mesh 34. Since mesh size of mesh 34 is preferably smaller, greater resistance is met by roots thereat, and the plant begins to develop hair roots that attach to mesh 34 as they continue to grow down from utility 31 (into apparatus 21, for example). This provides a firm bedding for the roots at mesh 33 and 34 and causes the plant to grow straight (toward its light source).

While a variety of shapes and configurations could be conceived, in particular as shown herein spacer 39 is preferably a ring shaped collar having blunt surfaces at ends 35 and 37. The inside and outside diameter of spacer 39 at ends 35 and 37 may vary as required by the particular application (a 0.75 inch inside diameter will be adequate for most single plantings). In such case, the diameter of mesh swathes 33 and 34 should be at least as great as the inside diameter of spacer 39. Retainers 45 and 47 in such case include a ring shaped body 55 of a size to fit snugly over ends 35 and 37 of spacer 39. Annular retaining lip 57 extends from one end of the ring shaped body 55 of retainers 45/47, inwardly at opening 59 defined through retainers 45/47, thus providing an end cap with openings 59 in correspondence with passageway 41

of spacer 39 when retainers 45/47 are associated with
spacer 39. By this means, mesh 33/34 are anchored
between the blunt surfaces at ends 35/37 of spacer 39 and
retainer lips 57 of retainers 45/47. To facilitate ready
5 application and removal of retainers 45/47, the retainers
should be made of a resilient but yieldable material
(many types of non-volatile thermoplastic would suffice
in this application). Spacer 39 should be of a firmer
material (metal, plastic or the like).

10 A second embodiment 61 of a utility of the seed
germination and plant supporting utility 17 of this
invention is shown in FIGURE 4 that provides more
extensive root support for a plant germinated therein. In
this embodiment, spacer 39 includes first and second
15 spacer components 63 and 65, each defining a part of
central opening/passageway 41. As before, mesh 33 and 34
are held spaced apart a selected distance by spacer
component 63 of spacer 39. Fabric mesh swathe 67 is
positioned at end 37 at spacer component 65 of spacer 39.
20 Each spacer component 63/65 has an interfacing surface 69
between which mesh 34 is retained, the spacer components
being held together thereat by retainer 71 (in this
particular embodiment, a ring shaped retainer made to fit
tightly at each interfacing end of components 63/65).

Mesh 67 and mesh 33 are anchored utilizing retainers 45 and 47 as heretofore described, mesh 67 and mesh 34 being thus held a selected distance apart by spacer component 65 of spacer 39.

5 Mesh size of mesh 67 should preferably be smaller or the same as mesh size of mesh 34 (which is smaller than mesh size of mesh 33). Larger plants requiring more extensive root support may benefit from the third tier supporting mesh as shown in FIGURE 4. As may be
10 appreciated, additional tiers may be added (though it is felt that such will be rarely necessary for most applications).

 Turning now to FIGURES 5A and 5B, containment and feeding apparatus 21 includes basin 75 for containing
15 fluid (water vapor, liquid water and/or water/vapor/nutrient mixture), submersible pump 77 having power cord 79 connected with user settable timer 81 (for timing and activating the pump in duration selected on/off cycles), and misting arm 83 connected through tube
20 85 to pump 77. Misting arm 83 distributes pumped water/nutrient held in basin 75 as a mist through jets 87 (flat jets 87a and corner jets 87b being provided) to the roots of plants held in the utility and exposed in chamber 91 of basin 75 or at seeds and/or seedlings

developing at a utility 31/61. Misting arm 83 is held at basin 75 on brackets 93 mounted within chamber 91 of the basin. An upper support rim 95 provides rigidity and strength at the upper opening 24 to chamber 91 of basin 75. The various components may be constructed of conventional materials suitable to their task.

Plant positioning structure 23 (FIGURE 5B) includes horizontal table 97 connected with leg structures 99 and 101 (made of plastic or light metal pipe, for example, and held at table 97 through openings 102 by threaded caps 103 engageable with matable threads at the leg structures 99/101). Table 97 rests on support rim 95 of basin 75 of apparatus 21 with leg structures 99/101 within chamber 91 when installed, and is readily removable therefrom, structures 99/101 holding roots spaced from a selected resting surface when table 97 is freestanding (thus protecting plant root growth). The plurality or receiving stations 25 are voids in table 97 sized and shaped to receive the various platforms 27 and/or filler blanks 29 (various sizes and shapes could be conceived of). Each station 97 is configured with a rim shelf 105 around the void upon which platforms 27 or blanks 29 are supported in the void.

Filler blanks 29 are provided merely to cap an unused station 25 to avoid loss of fluid therethrough. Removable plant maintenance platforms 27 are provided to hold plants and/or plant cuttings, and include four basic types (all as shown in greater detail in FIGURES 6 through 10): single unit platforms 107 (as shown herein configured for larger plants) and multi-purpose multiple unit platforms 109, both of which may be utilized with a utility 31/61; and cuttings support platforms 111 and/or 112.

Multi-purpose, multiple unit platform 109 (FIGURE 6) includes a plurality of openings 113 through platform wall 115 sized and shaped to receive a particular utility 31/61 therein. Each opening 115 may be utilized for cuttings. However, each opening 115 includes support lip 117 at the bottom of opening 115 upon which utility 31/61 when in use rests allowing roots thereat to be exposed through the bottom of opening 115 to chamber 91 of basin 75 of apparatus 21 (through the void defining station 25 at structure 23 holding platform 109). Filler blanks 121 are provided to cap unused openings 115 and/or to cap an opening 115 having a utility 31/61 therein while a seed is germinating thereon, as illustrated in FIGURE 5B (to

provide a moisture rich environment in the opening during germination of the seed).

Single unit platforms 107 (FIGURE 7, shown in use with a utility 31, though utility 61 or other multi-tiered utility as described hereinabove could be utilized, platform 107 also being usable for cuttings wherein no such utility is used) includes opening 125 through platform wall 127, the opening sized and shaped to receive a utility 31/61. Resilient yet deformable material retainer 129 and retainer lip 131 at the bottom of opening 125 (upon which a utility 31/61 rests) maintain assemblage of utility 31 and function in much the same way in this regard as retainers 45/47 (FIGURE 3). Retainer 129 is made of any suitable non-volatile material (various open or closed cell foam materials could be utilized), and includes opening 133 therethrough for receipt of the plant stem after plant germination (i.e., retainer 129 is applied around a seedling after sufficient growth has occurred). Plugs similar in structure to retainer 129 can be configured for use in any of the platform openings shown herein to provide cuttings support (without use of a full utility 31/61) and/or further seedling support (with a utility 31/61).

The plant stem is positioned by deformation of retainer 129 to open the retainer along the entire length of access slit 135 allowing access to opening 133. In cases where a plant is of significant size and/or is weak stemmed (or "leggy"), further support may be necessary. In such cases, support rod 137 held in stake cavity 139 formed in platform wall 127 can be utilized to further support the plant.

The platform embodiments shown in FIGURES 8 through 10, while primarily designed for use with cuttings, could also be adapted for use with utilities 31/61 of this invention. FIGURE 8 shows a first embodiment 111 of a cuttings support platform. In order to more gently handle cuttings and reduce cuttings damage, both during placement in the platform and during removal after root formation, platform 111 includes three readily disassociable wall segments 141, 143 and 145 (as few as two segments or as many segments as desired could be provided in various configurations of support platform 111, as may be appreciated). Guide and mounting pins 147 are embedded in segment 141 and matable mounting holes 149 are formed in segments 143 and 145 (only the two at segment 145 are shown, it being understood that similar structure is provided at segment 143). Each wall

segment, at its interface with an adjacent segment,
includes portions 151 defining, with its opposite
portions 151 (at the adjacent wall segment), openings 153
through platform 111 when the segments are assembled (see
5 FIGURE 5B).

A second embodiment of a readily accessible cuttings
support platform 112 is illustrated in FIGURES 9 and 10.
Platform 112 is a unitary structure made of resilient yet
deformable non-volatile material (various open or closed
10 cell foam materials or rubber could be utilized, for
example), and is sized to fit an appropriate receiving
station 25 at table 97. A plurality of openings 163 are
formed therethrough along access slits 165. The openings
and slits are formed so that three segments 167, 169 and
15 171 are provided (a lesser or greater number of segments
can be formed utilizing the arrangements taught herein).
A portion of each opening 163 is located along the slits
at each adjacent segment (in a similar relationship as
utilized for the openings defined by wall segments shown
20 in FIGURE 8), and the slits are discontinuous toward one
side 173 of platform 112 (with the segments thus
remaining associated thereat along side 173 as if
hinged).

Cuttings are preferably inserted into openings 163 while platform 112 is undeformed (preferably in position at a receiving station 25 at table 97). For removal of the cuttings from openings 163, platform 112 is manually
5 deformed to separate segments 167, 169 and/or 171 from each other along access slits 165 (as shown in FIGURE 10) allowing access to openings 163, the platform readily regaining its shape and utility upon release.

The sizes, shapes and number of plant accommodating
10 openings of the various platforms 27 described hereinabove may vary depending upon application, ease of manufacture, and/or aesthetic considerations.

As may be appreciated from the foregoing, this invention provides utilities for the propagation of
15 plants in a system free of traditional root supporting media. The utilities are flexible in use, easy to manage and clean, are suitable for use by hobbyists, scientists, horticulturists and the like, and may be maintained inside the home, on patios, in greenhouses, and/or by
20 commercial farming operations both indoors and outdoors. For many applications, utilities 31/61 may include reusable parts (retainers 55 and/or spacers 39, for example). For other applications (in particular organic farming) utilities 31/61 will be entirely biodegradable

(with retainers 55 and spacers 39 made of pulp fiber material, for example).